

DVX500



DPX ROOF WINDOW

Applicable

- In public and domestic buildings
- In heated, inhabited rooms
- In roof pitch range of 15°-90°
- Suitable on all roofings with proper flashing

Features

- Centre pivot
- Ventilation valve
- Toughened outer glass
- Slim frame
- Elegant bottom handle
- Two passive ventilation positions via handle
- Easy installation
- 10 year guarantee

Material | Wood and finishing

- Kiln-dried laminated pine wood
- Timber from PEFC certified forests
- Knot free visible surfaces
- Fungicide protection
- Acrylic lacquer

Cover parts

- Aluminium, lacquered, RAL 7043

Handle

- Ergonomically designed moulded zinc handle, lacquered

Hinge

- Pivot hinge

VARIANT	500
Pane	
Construction	4-16-4H
24 mm double glazing	■
Low E	■
Gas (argon)	■
Toughened	■
Ug (W/m²K)	1.1
Total solar energy transmittance	0.60
Uw (W/m²K)	1.5
Water tightness	E1200
Air permeability	Class 3
Resistance to wind load	Class C4
Sound reduction	30 (-1,-5) dB
Colour	
Natural wood	■

MEASURES								
CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m²
DVXC2A	55 x 78 cm	55 cm	77,8 cm	39,8 cm	64,9 cm	37,3 cm	59 cm	0.220
DVXC4A	55 x 98 cm	55 cm	97,8 cm	39,8 cm	84,9 cm	37,3 cm	79 cm	0.295
DVXF6A	66 x 118 cm	66 cm	117,8 cm	50,8 cm	104,9 cm	48,3 cm	99 cm	0.478
DVXM4A	78 x 98 cm	78 cm	97,8 cm	62,8 cm	84,9 cm	60,3 cm	79 cm	0.476
DVXM6A	78 x 118 cm	78 cm	117,8 cm	62,8 cm	104,9 cm	60,3 cm	99 cm	0.597
DVXM8A	78 x 140 cm	78 cm	139,8 cm	62,8 cm	126,9 cm	60,3 cm	121 cm	0.729
DVXS6A	114 x 118 cm	114 cm	117,8 cm	98,8 cm	104,9 cm	96,3 cm	99 cm	0.953

FLASHING COMPATIBILITY TABLE		
WINDOW SIZE CODE	SLATE	TILE
C2A	SFXC2A	TFXC2A
C4A	SFXC4A	TFXC4A
F6A	SFXF6A	TFXF6A
M4A	SFXM4A	TFXM4A
M6A	SFXM6A	TFXM6A
M8A	SFXM8A	TFXM8A
S6A	SFXS6A	TFXS6A

BLIND COMPATIBILITY TABLE	
BLACKOUT	ROLLER
RURC2A	RARCXA
RURC4A	RARCXA
RURF6A	RARFXA
RURM4A	RARMXA
RURM6A	RARMXA
RURM8A	RARMXA
RURS6A	RARSXA